

Ready for the season.



[ CODENAME ]

# FRUTTETO STAGE V



**SAME**

# FRUTTETO

Frutteto		90	95	100	105	115
Frutteto S						
Frutteto V						
<b>ENGINE</b>						
Model		FARMotion 35	FARMotion 45	FARMotion 35	FARMotion 45	FARMotion 45
Emission level		Stage V				
Aspiration		Turbo Intercooler				
Injection @ pressure	Type	Common Rail@2.000 bar				
Cylinders/Displacement	n°/cc	3/2887	4/3849	3/2887	4/3849	4/3849
Max. power (ECE R120)	kW/hp	67/91	70/95	75/102	78/106	85/116
Power at rated speed (ECE R120)	kW/hp	63.5/86	66.4/90	71.1/97	74/101	80.6/110
Max. torque @1.400 rpm	Nm	372	389	417	433	472
Fuel tank capacity (with front lift/PTO) - Frutteto	l	81 (61)	81 (61)	81 (61)	81 (61)	81 (61)
Fuel tank capacity (with front lift/PTO) - Frutteto S/V	l	75 (55)	75 (55)	75 (55)	75 (55)	75 (55)
XL Fuel tank capacity (with front lift/PTO)	l	100 (80)	100 (80)	100 (80)	100 (80)	100 (80)
AdBlue tank capacity	l	13	13	13	13	13
<b>TRANSMISSION - MECHANICAL SHUTTLE</b>						
Number of speed - 4 gears transmission*		12+12 or 24+12 (with mechanical splitter) or 24+24 (with HI-LO 2-Powershift steps)				
Max. speed - 4 gears transmission*	km/h	40				
Number of speed - 5 gears transmission		15+15 or 30+15 (with mechanical splitter) or 30+30 (with HI-LO 2-Powershift steps) or 45+45 (with HML 3-Powershift steps)				
Max. speed - 5 gears transmission	km/h	40 @ eco**				
<b>TRANSMISSION - POWERSHUTTLE</b>						
Number of speed - 5 gears transmission		15+15 or 30+15 (with mechanical splitter) or 30+30 (with HI-LO 2-Powershift steps) or 45+45 (with HML 3-Powershift steps)				
Max. speed - 5 gears transmission	km/h	40 @ eco**				
<b>PTO</b>						
PTO speeds		540/540E or 540/540E/1000 or 540/540E/Ground Speed				
Rear AUTO PTO function		o	o	o	o	o
Front PTO 1000		o	o	o	o	o
<b>LIFT</b>						
Electronic rear lift		▲	▲	▲	▲	▲
Vibration damping function		▲	▲	▲	▲	▲
Rear linkage lifting capacity - Frutteto (STD/OPT)	kg	3130/3940	3130/3940	3130/3940	3130/3940	3130/3940
Rear linkage lifting capacity - Frutteto S		2600	2600	2600	2600	2600
Rear linkage lifting capacity - Frutteto V		2600	2600	2600	2600	2600
Hydraulic right tie rod and stabilizers		o	o	o	o	o
Front lift (1.500 kg)		o	o	o	o	o
<b>HYDRAULICS</b>						
Open centre hydraulic system (STD)	l/min	56	56	56	56	56
Open centre hydraulic system with double pump (OPT)	l/min	68	68	68	68	68
Rear spool valves (STD/OPT)	n°	2/3	2/3	2/3	2/3	2/3
Flow regulator		o	o	o	o	o
Rear free return		▲	▲	▲	▲	▲
Mid-mounted hydraulic ways - duplicated from rear (OPT)	n° of ways	2/4/5	2/4/5	2/4/5	2/4/5	2/4/5
Mid-mounted free return		o	o	o	o	o
<b>BRAKES</b>						
Front axle with brakes		▲	▲	▲	▲	▲
Hydraulic trailer brake		o	o	o	o	o
ABS Socket		o	o	o	o	o
<b>FRONT AXLE</b>						
Electrohydraulic engagement for 4WD and Diff.Lock		▲	▲	▲	▲	▲
Auto 4WD		o	o	o	o	o
Independent steering pump	l/min	42	42	42	42	42
Steering Double Displacement (SDD)		o	o	o	o	o
<b>ACTIVEDRIVE FRONT AXLE (OPT)</b>						
Adaptive-Damping, Active Self-Leveling functions		▲	▲	▲	▲	▲
Anti-Dive, Anti-Roll functions		▲	▲	▲	▲	▲
Differential Traction Control (DTC)		▲	▲	▲	▲	▲

\*Not available for Frutteto V

\*\* According to rear tyres size

▲ STD

o OPT

- Not available

<b>Frutteto</b>		<b>90</b>	<b>95</b>	<b>100</b>	<b>105</b>	<b>115</b>
<b>Frutteto S</b>						
<b>Frutteto V</b>						
<b>CAB</b>						
4 pillar cab		▲	▲	▲	▲	▲
Flat floor		▲	▲	▲	▲	▲
InfoCentre		▲	▲	▲	▲	▲
Adjustable steering column		○	○	○	○	○
Mechanical suspended seat		▲	▲	▲	▲	▲
Pneumatic suspended seat		○	○	○	○	○
Suspended on Hydro Silent-Block		▲	▲	▲	▲	▲
Cat.4 filtration system		○	○	○	○	○
Liftable rear top roof		○	○	○	○	○
Rounded top windscreen		▲	▲	▲	▲	▲
Halogen working lights (STD)	n°	4	4	4	4	4
LED working lights (OPT)	n°	4/6	4/6	4/6	4/6	4/6
Mechanical cross lever - 2 spool valve controls		○	○	○	○	○
Smartphone holder and 2 USB plugs		○	○	○	○	○
Radio		○	○	○	○	○
Jump start		○	○	○	○	○
External controls for PTO and lift		○	○	○	○	○
CTM - Telematics module		○	○	○	○	○

<b>Frutteto</b>		<b>90</b>	<b>95</b>	<b>100</b>	<b>105</b>	<b>115</b>
<b>DIMENSION</b>						
Wheelbase	mm	2044	2174	2044	2174	2174
Max. length	mm	3670	3800	3670	3800	3800
Total height - CAB	mm	2495	2495	2495	2495	2495
Height at bonnet	mm	1475	1475	1475	1475	1475
Width (min.-max.)	mm	1441-1671	1441-1671	1441-1671	1441-1671	1441-1671
Weight - CAB	kg	3290-3880	3515-4105	3290-3880	3515-4105	3515-4105
Total admissible load	kg	5200	5200	5200	5200	5200


<b>Frutteto S</b>		<b>90</b>	<b>95</b>	<b>100</b>	<b>105</b>	<b>115</b>
<b>DIMENSION</b>						
Wheelbase	mm	2086	2216	2086	2216	2216
Max. length	mm	3670	3800	3670	3800	3800
Total height - CAB	mm	2420	2420	2420	2420	2420
Height at bonnet	mm	1475	1475	1475	1475	1475
Width (min.-max.)	mm	1269-1517	1269-1517	1269-1517	1269-1517	1269-1517
Weight - CAB	kg	3265-3865	3320-3920	3265-3865	3320-3920	3320-3920
Total admissible load	kg	5000	5000	5000	5000	5000

<b>Frutteto V</b>		<b>90</b>	<b>95</b>	<b>100</b>	<b>105</b>	<b>115</b>
<b>DIMENSION</b>						
Wheelbase	mm	2086	2216	2086	2216	2216
Max. length	mm	3670	3800	3670	3800	3800
Total height - CAB	mm	2395	2395	2395	2395	2395
Height at bonnet	mm	1440	1440	1440	1440	1440
Width (min.-max.)	mm	1166-1317	1166-1317	1166-1317	1166-1317	1166-1317
Weight - CAB	kg	3180-3690	3235-3745	3180-3690	3235-3745	3235-3745
Total admissible load	kg	5000	5000	5000	5000	5000

**FRTT**

[STAGE V]

FRUTTETO S/V  
90 | 95 | 100  
105 | 115



### TRANSMISSION

- Mechanical shuttle or PowerShuttle with SenseClutch
- From 12+12 up to 45+45 with 3-Powershift steps (HML)
- New 24+24 or 30+30 Hi-Lo transmissions

### FARMOTION 35 AND 45

- FARMotion 35 and 45 engines, 3 and 4 cyl
- FARMotion 45 features the highest displacement in the segment
- FARMotion 35 allows short wheelbase for high maneuverability
- Max. power up to 116 HP
- Tapered and sloping bonnet gives excellent agility and visibility

### CAB

- Flat floor and no central tunnel
- Hydro Silent-Block suspension
- Cat.4 filtration and pressurization system
- Adjustable steering column
- CTM connectivity

### AXLES

- Fixed front axle or ActiveDrive
- True 4-wheel braking
- SDD and Auto4WD function available

### NEW HYDRAULIC SYSTEM

- 3 rear spool valves with free return
- Up to 5 mid-mounted hydraulics ways
- Mechanical cross lever for 2 spool valves control
- Single pump with 56 l/min or Double pump with 68 l/min oil flow



The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice.  
Cod. 308.9004.3.1-0 - 02/2022

To find out more, visit [same-tractors.com](http://same-tractors.com) or talk to your dealer.



SAME is a brand of SDF



**SAME**